







DESIGN PARAMETE	RS
Speed Limit	50 km/l
Road Classification	1(iii)
Roadworks type	В
Number of advance signs	2
Sign visibility	50m
Distance between signs	20m
Taper at lane	N/A
Taper at hard shoulder	N/A

Sign size (diamond)	600mm
Sign size (circular)	600mm
Minimum Cone size	750mm
Cone spacing at tapers	3m
Cone spacing longitudinal	3m
Lateral Safety Zone	0.5m
Longitudinal Safety Zone	5m
Minimum lane width	3.0m

LEGEND	GENERAL NOTES 1) All information contained in this drawing (including digital data) should be
Local Access Works in Place Traffic sign Traffic cones Diversion Route A Diversion Route B	checked and verified prior to any stage of construction; 2) All works are to be carried out in accordance with local authority requirements and are to be included in the site-specific safety & health plan 3) Site inspections and maintenance of the traffic management layout is to be agreed with local authority to ensure the safety and integrity of the design; 4) Contractor to carry out a site risk assessment prior to the installation of any traffic management plan to ensure that conditions reflect those considered for design post submission; 5) Contractor shall be responsible for the provision of ramp access at any change in road surface level where traffic runs on a temporary surface, and for pedestrian/cycle ramps where footpath/cycle-ways have a level discontinuity as per result of the works.

Drn	Chk	Арр	Drn	BC	Project	
			Chk	DS	ROSSES POINT VILLAGE CATCHMENT A	
			Арр	DH		
			Date	20-07-2022	Title	
			Scale	A1 NTS A3 NTS	TRAFFIC MANAGEMENT PLAN PHASE 1 ROAD CLOSURE	
			Stage CON	ISTRUCTION	Drawing No C22063_01_004 Rev 0	